

iD Click Ultimate 55-70 & 55-70^{PLUS}

LUXURY VINYL TILES

Specification
model

2019

The selected flooring similar to iD Click Ultimate belongs to the compact vinyl floors category with a Rigid Composite Core layer manufactured through extrusion process and a density of 2000kg/m³.

It also contains an integrated acoustic backing of 19db.

It is available in planks (17.60x121.30 cm; 20.05x120.00 cm, 24.30x150.00 cm) and tiles (24.30x48.60 cm; 48.00x48.00 cm; 48.00x96.00 cm) formats

The product is available with a wear-layer of 0,70mm (iD Click Ultimate 70) and a wear-layer of 0,55mm (iD Click Ultimate 55). The wear layer is reinforced with a PU treatment, which permanently suppresses any wax and regenerating polish spray maintenance operations.

It has a static indentation resistance $\leq 0,02\text{mm}$ and a dimensional stability $\leq 0,05\%$ according to EN ISO 23 999.

iD Click Ultimate can sustain heavy static and rolling loads up to 800 kg (iD Click Ultimate 70) or 500Kg (iD Click Ultimate 55).

Its emission rate of volatile organic compounds in air is less than 100 $\mu\text{g} / \text{m}^3$ (COVT after 28 days).

iD Click Ultimate comes with a 10 Year warranty.